



TOLERANCES (inch)		
DIAMETER	D ₁	D ₂
3/4 - 1	-0.00040/-0.00200	h6

TOLERANCES (mm)		
DIAMETER	D ₁	D ₂
12 - 25	-0,010/-0,050	h6

CORNER RADIUS TOLERANCES (inch)
R = +/- 0.0018

CORNER RADIUS TOLERANCES (mm)
R = +/- 0,03

**43APR
(FRACTIONAL)**

Cutting Diameter D ₁	Length of Cut L ₂	Overall Length L ₁	Shank Diameter D ₂	Reach L ₃	Corner Radius R	Ti-NAMITE-B (TiB ₂) EDP No.
3/4	1-3/8	4-1/4	3/4	2-3/8	.030	34000
3/4	1-3/8	4-1/4	3/4	2-3/8	.060	34001
3/4	1-3/8	4-1/4	3/4	2-3/8	.090	34002
3/4	1-3/8	4-1/4	3/4	2-3/8	.120	34003
3/4	1-1/4	4-7/8	3/4	3	.030	34004
3/4	1-1/4	4-7/8	3/4	3	.060	34005
3/4	1-1/4	4-7/8	3/4	3	.090	34006
3/4	1-1/4	4-7/8	3/4	3	.120	34007
1	1-3/4	4-1/2	1	2-1/2	.030	34008
1	1-3/4	4-1/2	1	2-1/2	.060	34009
1	1-3/4	4-1/2	1	2-1/2	.090	34010
1	1-3/4	4-1/2	1	2-1/2	.120	34011
1	1-1/2	5-1/4	1	3-1/4	.030	34012
1	1-1/2	5-1/4	1	3-1/4	.060	34013
1	1-1/2	5-1/4	1	3-1/4	.090	34014
1	1-1/2	5-1/4	1	3-1/4	.120	34015

**43MAPR
(METRIC)**

Cutting Diameter D ₁	Length of Cut L ₂	Overall Length L ₁	Shank Diameter D ₂	Reach L ₃	Corner Radius R	Ti-NAMITE-B (TiB ₂) EDP No.
12,0	18,0	83,0	12,0	38,0	-	44650
12,0	18,0	83,0	12,0	38,0	2,0	44685
12,0	18,0	83,0	12,0	38,0	3,0	44686
12,0	18,0	83,0	12,0	38,0	4,0	44687
16,0	24,0	92,0	16,0	51,0	-	44652
16,0	24,0	92,0	16,0	51,0	2,0	44688
16,0	24,0	92,0	16,0	51,0	3,0	44689
16,0	24,0	92,0	16,0	51,0	4,0	44690
20,0	30,0	86,0	20,0	45,0	-	44646
20,0	30,0	86,0	20,0	45,0	3,0	44647
20,0	30,0	86,0	20,0	45,0	4,0	44648
20,0	30,0	86,0	20,0	45,0	5,0	44649
20,0	35,0	104,0	20,0	64,0	-	44653
20,0	35,0	104,0	20,0	64,0	3,0	44691
20,0	35,0	104,0	20,0	64,0	4,0	44692
20,0	35,0	104,0	20,0	64,0	5,0	44693
25,0	35,0	108,0	25,0	55,0	3,0	44809
25,0	35,0	108,0	25,0	55,0	4,0	44810
25,0	35,0	108,0	25,0	55,0	5,0	44811
25,0	35,0	140,0	25,0	80,0	-	44654
25,0	35,0	140,0	25,0	80,0	3,0	44694
25,0	35,0	140,0	25,0	80,0	4,0	44695
25,0	35,0	140,0	25,0	80,0	5,0	44696
25,0	35,0	140,0	25,0	90,0	3,0	44645

Available on request: • JetStream Technology • Side exits for MQL applications