



140 5xD

FRACTIONAL & METRIC SERIES

CONTINUED

CUTTING DIAMETER	DECIMAL EQUIV.	TAP SIZE REFERENCE ONLY	mm					EDP NO. Ti-NAMITE-A (AITiN)
			SHANK DIAMETER	OVERALL LENGTH	FLUTE LENGTH	CLEARED LENGTH	SHANK LENGTH	
D ₁			D ₂	L ₁	L ₂	L ₃	L ₄	
27/64	0.4219	1/2-13	12,0	118,0	71,0	56,0	45,0	51929
10,8 mm	0.4252	M12 X 1,25	12,0	118,0	71,0	56,0	45,0	63975
10,9 mm	0.4291		12,0	118,0	71,0	56,0	45,0	63976
11,0 mm	0.4331	M12 X 1	12,0	118,0	71,0	56,0	45,0	63977
11,1 mm	0.4370		12,0	118,0	71,0	56,0	45,0	63978
7/16	0.4375	1/4-18NPT	12,0	118,0	71,0	56,0	45,0	51930
11,2 mm	0.4409		12,0	118,0	71,0	56,0	45,0	63979
11,3 mm	0.4449		12,0	118,0	71,0	56,0	45,0	63980
11,4 mm	0.4488		12,0	118,0	71,0	56,0	45,0	63981
11,5 mm	0.4528	M12 X 0,5	12,0	118,0	71,0	56,0	45,0	64000
11,6 mm	0.4567		12,0	118,0	71,0	56,0	45,0	63982
11,7 mm	0.4606		12,0	118,0	71,0	56,0	45,0	63983
11,8 mm	0.4646		12,0	118,0	71,0	56,0	45,0	63984
11,9 mm	0.4685		12,0	118,0	71,0	56,0	45,0	63985
15/32	0.4688	1/2-28,0	12,0	118,0	71,0	56,0	45,0	51932
12,0 mm	0.4724	M14 X 2	12,0	118,0	71,0	56,0	45,0	63986
31/64	0.4844	9/16-12	14,0	124,0	77,0	60,0	45,0	51933
12,5 mm	0.4921	M14 X 1,5	14,0	124,0	77,0	60,0	45,0	63987
1/2	0.5000		14,0	124,0	77,0	60,0	45,0	51934
12,8 mm	0.5039	M14 X 1,25	14,0	124,0	77,0	60,0	45,0	63988
13,0 mm	0.5118	M14 X 1	14,0	124,0	77,0	60,0	45,0	63989
33/64	0.5156	9/16-18	14,0	124,0	77,0	60,0	45,0	51935
13,5 mm	0.5315	5/8-11	14,0	124,0	77,0	60,0	45,0	64001
13,8 mm	0.5433		14,0	124,0	77,0	60,0	45,0	63990
14,0 mm	0.5512	M16 X 2	14,0	124,0	77,0	60,0	45,0	63991
9/16	0.5625		16,0	133,0	83,0	63,0	48,0	51937
14,5 mm	0.5709	M16 X 1,5	16,0	133,0	83,0	63,0	48,0	63992
37/64	0.5781	5/8-18	16,0	133,0	83,0	63,0	48,0	51938
14,8 mm	0.5827		16,0	133,0	83,0	63,0	48,0	63993
15,0 mm	0.5906	M16 X 1	16,0	133,0	83,0	63,0	48,0	63994
15,5 mm	0.6102	M18 X 2,5	16,0	133,0	83,0	63,0	48,0	63995
15,8 mm	0.6220		16,0	133,0	83,0	63,0	48,0	63996
5/8	0.6250	11/16-16	16,0	133,0	83,0	63,0	48,0	51939
16,0 mm	0.6299		16,0	133,0	83,0	63,0	48,0	63997
21/32	0.6562	3/4-10	18,0	143,0	93,0	71,0	48,0	51940
11/16	0.6875	3/4-16	18,0	143,0	93,0	71,0	48,0	51941
3/4	0.7500	13/16-16	20,0	153,0	101,0	77,0	50,0	51942