



140 8xD

FRACTIONAL & METRIC SERIES

CONTINUED

CUTTING DIAMETER	DECIMAL EQUIV.	TAP SIZE REFERENCE ONLY	mm					EDP NO. Ti-NAMITE-A (AlTiN)
			SHANK DIAMETER	OVERALL LENGTH	FLUTE LENGTH	CLEARED LENGTH	SHANK LENGTH	
D ₁			D ₂	L ₁	L ₂	L ₃	L ₄	
27/64	0.4219	1/2-13	12,0	162,0	114,0	96,0	45,0	51825
10,8 mm	0.4252	M12 X 1,25	12,0	162,0	114,0	96,0	45,0	63653
10,9 mm	0.4291		12,0	162,0	114,0	96,0	45,0	63654
11,0 mm	0.4331	M12 X 1	12,0	162,0	114,0	96,0	45,0	63655
11,1 mm	0.4370		12,0	162,0	114,0	96,0	45,0	63656
7/16	0.4375	1/4-18NPT	12,0	162,0	114,0	96,0	45,0	51826
11,2 mm	0.4409		12,0	162,0	114,0	96,0	45,0	63657
11,3 mm	0.4449		12,0	162,0	114,0	96,0	45,0	63658
11,4 mm	0.4488		12,0	162,0	114,0	96,0	45,0	63659
11,5 mm	0.4528	M12 X 0,5	12,0	162,0	114,0	96,0	45,0	63660
11,6 mm	0.4567		12,0	162,0	114,0	96,0	45,0	63661
11,7 mm	0.4606		12,0	162,0	114,0	96,0	45,0	63662
11,8 mm	0.4646		12,0	162,0	114,0	96,0	45,0	63663
11,9 mm	0.4685		12,0	162,0	114,0	96,0	45,0	63664
15/32	0.4688	1/2-28	12,0	162,0	114,0	96,0	45,0	51827
12,0 mm	0.4724	M14 X 2	12,0	162,0	114,0	96,0	45,0	63665
31/64	0.4844	9/16-12	14,0	178,0	133,0	112,0	45,0	51828
12,5 mm	0.4921	M14 X 1,5	14,0	178,0	133,0	112,0	45,0	63666
1/2	0.5000		14,0	178,0	133,0	112,0	45,0	51829
12,8 mm	0.5039	M14 X 1,25	14,0	178,0	133,0	112,0	45,0	63667
13,0 mm	0.5118	M14 X 1	14,0	178,0	133,0	112,0	45,0	63668
33/64	0.5156	9/16-18	14,0	178,0	133,0	112,0	45,0	51830
13,5 mm	0.5315	5/8-11	14,0	178,0	133,0	112,0	45,0	63669
13,8 mm	0.5433		14,0	178,0	133,0	112,0	45,0	63670
14,0 mm	0.5512	M16 X 2	14,0	178,0	133,0	112,0	45,0	63671
9/16	0.5625		16,0	203,0	152,0	128,0	48,0	51831
14,5 mm	0.5709	M16 X 1,5	16,0	203,0	152,0	128,0	48,0	63672
37/64	0.5781	5/8-18	16,0	203,0	152,0	128,0	48,0	51832
14,8 mm	0.5827		16,0	203,0	152,0	128,0	48,0	63673
15,0 mm	0.5906	M16 X 1,5	16,0	203,0	152,0	128,0	48,0	63674
15,5 mm	0.6102	M18 X 2,5	16,0	203,0	152,0	128,0	48,0	63675
15,8 mm	0.6220		16,0	203,0	152,0	128,0	48,0	63676
5/8	0.6250	11/16-16	16,0	203,0	152,0	128,0	48,0	51833
16,0 mm	0.6299		16,0	203,0	152,0	128,0	48,0	63677
21/32	0.6562	3/4-10	18,0	222,0	171,0	144,0	48,0	51834
11/16	0.6875	3/4-16	18,0	222,0	171,0	144,0	48,0	51835
3/4	0.7500	13/16-16	20,0	243,0	190,0	160,0	50,0	51836